

STONE TECHNOLOGIES, CORP.  
PO BOX 2161, CLEVELAND, TN 37320-2161  
TEL. (423) 503 4490  
stonetechnologiescorp.com

## **CONCRETE SEALER X-2**

### **WATER-BASED**

*Forms an invisible protective barrier on concrete and masonry surfaces to make them harder, dustproof, oil, acid and moisture resistant.*

**Directions:** Always test the surface to be treated in an inconspicuous area to ensure proper absorption by your concrete prior to applying this product to the whole area. Brush, roll or spray onto the surface to be treated. Allow to dry for 2 to 4 hours and then re-apply using the same procedure. Allow to cure overnight. If any white residue forms on the surface remove it immediately with a stiff brush or pressure washer.

**DANGER:** *Keep out of reach of children and animals.  
Always wear gloves and protective goggles when using this product.*

**1 Gallon (3.78L) 040110**

#### **1.FIRST AID**

**Eyes:** Flush with cool water for at least 15 minutes. Call a physician.

**Skin:** Wash thoroughly with soap and water. Call a physician.

**Ingestion:** Call a physician. Never give anything by mouth to an unconscious person.

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration preferably mouth to mouth. Call a physician.

#### **2.SPILL CONTROL**

Eliminate all ignition sources and keep public away. Recover free product with absorbent materials and dispose of in accordance with local, State and Federal Regulations.

Keep product out of sewers and water courses.

#### **3. PROTECTIVE EQUIPMENT**

Wear safety glasses or goggles and recommended protective gloves.

If exposure exceeds TLV, wear NIOSH/MSHA approved respirator.

#### **4. PRECAUTIONS**

Do not get in eyes, on skin or clothing. Do not take internally.

Wash thoroughly after handling.

#### **5. GENERAL INSTRUCTIONS**

Before using this product read Material Safety Data Sheet (MSDS) for more detailed information. An MSDS is available upon request from Stone Technologies, Corp.

**Note:** Emptied container contains product residue.

The information contained in this label applies to the product as shipped.

**HMIS Rating: H = 2 F = 0, R = 0, PP = X**

**For emergency health and safety information contact: (423) 503 4490**

#### **DISCLAIMER**

The information contained herein is based on data available to us and is believed to be accurate. However, Stone Technologies, Corp. makes no express or implied warranty of merchantability or fitness for a particular use. Handling, storage and use of this product by the buyer or user are beyond the control of Stone Technologies, Corp. Risks such as ineffectiveness or other unintended consequences resulting from but not limited to failure to follow label directions will be assumed by the buyer or user. In no case will seller be held liable for consequential, special or indirect damages resulting from the handling, storage or use of this product.