



STONE TECHNOLOGIES, CORP.
PO Box 2161, Cleveland, TN 37320
Phone: 423-503-4490/423-400-7313
www.stonetechnologiesinc.com

To whom it may concern,

Concrete Sealer X-3 is an environmentally friendly silicone polymer emulsion which when applied to concrete will make it become repellent to water, oil and petroleum based compounds including diesel fuel.

The above statement is based on the following parameters being met by the concrete to be treated;

- It must be absorbent. This is tested with a single droplet of water in several areas. The water droplet must be absorbed by the concrete within 20-30 seconds. If the water does not absorb then chemical etching must be performed prior to application
- Concrete was never previously sealed or coated which may hinder penetration of the sealer.
- Concrete is free of dirt, grime and contaminants.

Two applications of Concrete Sealer X-3 are required either with a medium nap roller or a sprayer.

The applications must be applied within 2 to 4 hours at 40 to 80 deg F (shorter time for higher temperature) and allowed to cure for 24 hours..

Concrete Sealer X-3 contains 0% (0 g/L) Volatile Organic Compounds (VOC) or solvents. It is considered to be environmentally friendly and does not release any harmful vapors into the atmosphere. All of the components in these products are listed on the TSCA inventory.

Michael A. Parry, President